

# LPG STANDALONE

## A compact and efficient solution

- > Lane orientation
- > 1 or 2 nozzles
- > External or internal hose with retraction
- > Small footprint



# Product specifications

The SK700-II LPG Standalone is one of the many modular designs available with the SK700-II series, so it fits seamlessly with the rest of the systems and solutions on your forecourt.

Technical Specifications	Standard Features	Options
Hydraulics	LPG hydraulics with 1 or 2 meters Electronic meter calibration Break away coupling – Elaflex	Solenoid valve: two stage dual flow for pre-set Shear valve
Electronics	Pulser Calculator LCD display (back lit) Dead man push button	Emergency stop button Automatic Temperature Compensation (selected countries) Pre set keypad Computer head door alarm Bolt-on CRIND ready Communication protocol options Electromechanical totaliser
Mechanical	Housing – painted steel Frame – hot galvanized sheet metal Hose Management – internal hose connection CR LPG nozzle – T3 OPW Hose – Elaflex	Stainless steel hose column and hydraulic panels Livery options on request Types of nozzles on request Nozzle lock Hose management system: external hose with rope retract

## Technical Characteristics & Performance

Environmental	<b>Climate:</b> Marine, tropical, industrial, polar   <b>Ambient temperature range:</b> -25°C to +50°C
Meter characteristics	<b>Displacement:</b> 0,500L   <b>Maximum flow rate:</b> 50L/min   <b>Minimum flow rate:</b> 5L/min   <b>Accuracy within the flow range:</b> ± 1%   <b>Maximum service pressure (operating pressure):</b> 25 bar
Electrical	230V (+10%; -15%), 50Hz ± 2Hz

